



PVC Resin MG8

>>Product Name: M-PVC RESIN MG8

>>Typical Properties

No	TYPE		MG8
1	GRADE		SUPER
2	STANDARD		HG/T4067-2008
3	AVERAGE POLYMERIZATION DEGREE		650-750
4	K-VALUE		55-59
5	BLACK SPOT ≤		16
6	VOLATILE MATTER AND MOISTURE% ≤		0.2
7	BULK DENSITY g/ml ≥		0.55
8	RESIDUAL%	PARTICLE SIZE% 0.25MM SIEVE ≤	2
		PARTICLE SIZE% 0.063MM SIEVE ≥	\
9	FISH HOLE NUMBER/400CM ≤		10
10	PLASTICIZER ABSORPTION ≥ PER 100G RESIN G.		13
11	WHITENESS 160 , 100 MIN %		74
12	FLOW ABILITY (S) ≤		14
13	VCM RESIDUALS PPM ≤		30

Technical Data Sheet

>> Special quality

Good flowability; Excellent softening ability

Good transparency, High insulativity ,Low amount of residue

>> Applications

Injection molded parts, hollow products, film, sheet

>> Package

The product is supplied in powder form in 25kg paper sacks., 16.5mt can be loaded in 20'FCL

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist.,Dalian, P.R.C