



Calcium Carbonate

>>Product Name: Calcium Carbonate GC-800

>>Typical Properties

Item	Test Method	Standard
Bulk density	ISO WD/HJH-7.6-0.1-2003	0.395 g/ml
Tamped density	Internal Method	0.791 g/ml
Specific gravity	Internal Method	2.8 g/ml
Specific surface	B.E.T	4512 cm ² /g
Moisture	202-O	0.29 %
Wet screen residual	AAS	99.92 %
MgO		0.15 %
Fe ₂ O ₃		0.02 %
CaCO ₃		98.5%
Loss on ignition at 1000°C	SKJX-4-13	42.85 %
PH	ISO WD/HJH-7.6-0.2-2003	9

>> Special quality

Identical grain size, low oil absorption value;

Reduce the cost if products;

Make products have good foamed effect;

Enhance hardness, rigidity, size stability, fire-retardance, glossiness of products

>>Applications

Used as filler in plastics and rubber, paper industry and paint industry.

>> Package

The product is supplied in powder form in 25kg paper sacks., 24mt can be loaded in 20'FCL

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist.,Dalian, P.R.C