

PVC Ca. Zn. One-pack Stabilizers

>>Product Name

Product: PKG008
Stabiliser type: Ca/Zn
Typical phr :4.0 − 6.0
Lubrication : ★★★★

Appearance: white or pale-yellowish Powder



>>Typical formulation

	Insulation	Sheathing
S-PVC K 65-70	100	100
PKG008	3.5 – 5.0	2.5 – 4.0
DOP/DINP/DIDP	40 - 50	50
CaCO ₃	40 - 60	60 - 80
ESBO	3	3

>> Special quality

PKG008 is nontoxic Ca/Zn compound stabilizer

Self-lubricative, and able to be used independently

With good long-term heat resistance, and can be used in general electric wires

Effectively resistant to sulfurization and climate

Better compatible with PVC and plasticizers

With high-level brightness and well initial staining

Cooperation with epoxidized soybean oil, yielding favorable synergetic results;

It is recommended to mix in a high speed mixer to 120°C and cool to 40°C.

>> Applications: Soft &Semi-rigid PVC Wires and Cable

>> **Package**: The product is supplied in powder form in paper sacks.

>> Suggestion

It should be kept from moister & sunshine during the transportation or storage. All batches are tested to ensure a consistent quality and a certificate of conformity can be supplied with each batch if requested. According to RoHS.

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist., Dalian, P.R.C