


PVC Ca. Zn. One-pack Stabilizers

>>Product Name

Product: PWG562 Stabiliser type: Ca/Zn Typical phr: 3.5 – 4.5 Metal Oxide (%):16.0min Heating Loss(%): 3.0max

Appearance: white or yellowish Powder



>>Typical formulation

Ingredient	PVC	CaCo3	TiO2	CPE	ACR	Stabilizer
Dosage	100	10-25	4.0-6.0	8-12	1.5-2.5	3.5-4.5

>> Special quality

PWG562 is nontoxic, odorless, Cadmium-free, odorless, Cadmium-free, Pb-free and environment; Good heat stability&lubricity, light stability, anti-polluting to vulcanization and weather resistance. With special coupled action, providing good dispersibility to fillings, increasing compatibility with resir improving product performance, reducing the abrasion, extending the service life of machine.

Good welding property and impact-resistance, it could improve the impact strength of the profile and strength of the door & window, improve the outdoor aging property of door and window products. it could make the profile extrusion processing with good property, improve product quality&percent of pass, thus reduce the comprehensive cost of the profiles;

With good initial coloring and stability in anaphase

Good anti-precipitation, and forming processing, stable during production, prolonging production circle; making the tube wall thick and thin equally; glossing appearance, increasing the bursting properties of water pressure foe the products

It is recommended to mix in a high speed mixer to 120 °C and cool to 40 °C.

>> **Applications**: Rigid profiled bar, window profile

>> **Package**: The product is supplied in powder form in paper sacks.

>> Suggestion

It should be kept from moister & sunshine during the transportation or storage. All batches are tested to ensure a consistent quality and a certificate of conformity can be supplied with each batch if requested. According to RoHS.

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist., Dalian, P.R.C