



MOREN INT'L(DALIAN) CO., LIMITED
Professional supplier for Plastic&Rubber materials

PVC Impact Modifier

>>Product Name

Acrylic Impact Modifier AIM 808

>>Typical Properties

Appearance	Powder
Bulk Density g/cm ³	0.50
Max. Torque N	30.5
Min. Torque N	15.0
Balance Torque N	26.5
Fusion Time S	66
Plastication Temp.	160℃
Tensile Strength	40.89
Notch Impact Strength	12.14

>> Special quality

Excellent Weatherability
Superior "Satin" Surface Finish
Good Low-Temperature Impact
Improved Processing ability
High Output

>> Applications

Profiles, sheets, pipes, pipe fitting, etc

>> Package

25kg/bag;1100kg/pallet ;11MTs in 20 feet container

>> Suggestion

The products are manufactured in the modern computer controlled plant in Shandong&Taipei in accordance with ISO 9001:2000 Standard. All batches are tested to ensure a consistent quality and a certificate of conformity can be supplied with each batch if requested.

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist.,Dalian, P.R.C