



PVC Processing Aid

>>Product Name

Acrylic Processing Aid APA 175

>>Typical Properties

Appearance	White free-flowing powder
Granularity(throughput efficiency of 40 mesh)(%)	≥ 98
Volatiles(%)	≤ 1.0
Viscosity (η)(Ubbelohde Viscometer)	2.0-3.0
Molecular weight (million)	0.4~0.8

>> Special quality

APA 175 is a newly developed lubricating processing aids with a unique function,

Good metal release properties

To prolong the working time

To reduce the plate-out on the surface of machine

Excellent transparency without moving

Higher output and better flowability

Increase the surface quality of PVC products

>> Applications

APA175 is suitable to all kinds of products of PVC, such as rigid calendered film and sheets, rigid bottles, window profiles etc. Addition levels for this application are 0.5-1 phr (PVC 100 phr).

>> Package

25kg/bag;1100kg/pallet ;11MTs in 20 feet container

>> Suggestion

All batches are tested to ensure a consistent quality and a certificate of conformity can be supplied with each batch if requested.

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist.,Dalian, P.R.C

