



External Lubricant-GC74

>>Product Name: External Lubricant GC74

>>Typical Properties

| No | Item | Standard |
|----|--------------------------------|-------------|
| 1 | Bulk Density,g/cm ³ | 0,880~0.930 |
| 2 | Dioptric index,(80°C) | 1.420~1.470 |
| 3 | Viscosity, mPa.S(80°C) | 40~80 |
| 4 | Acid value, mg KOH/g | 12max |
| 5 | Iodine Value,g/100g | 2max |

>> Special quality

GC74 IS multi-alcoholization fatty acid ester, it can be used as external lubricant with good transparency and dispersancy.

It is specially suitable for transparent soft products.

It is light yellow or milk-white chip

It can be dissolved in hot alcohol, tri-butyl phosphate and chloroform, but not in water and alcohol.

Good metal release and persistence.

>> Applications

Transparent sheet, pellet, shrinkable film, kink film and other opaque products.

>> Package

The product is supplied in solid form in 25kgs PP woven bag

>> Storage

To be stored in cool and ventilated warehouse, avoid direct exposure to sunlight.

>> More Than Additives

Taiwan Factory: No.22, Te-Hui Street, Taipei, Taiwan, R.O.C.

Dalian Factory: A Building 22, Wanli West Street, E.T.D.A. Dist.,Dalian, P.R.C